

Foshan Ultraton Engineering Machinery Co., Ltd

# 2 Axles 20ft Flatbed Container Transport Semi Truck Trailer



Ultratons'2 axles 20ft Flatbed Semi Trailer is a commonly seen model equipped with 2 pieces of semi-trailer axles for standard 20ft container. It can be modified according to customer's requirement.

### **Overview of 2 Axles 20ft Flatbed Container Transport Semi Truck Trailer**

- Scientific design with advanced computer-aided design software, finite element analysis of the frame according to vehicle load quality requirements
- Flange and web width & thickness could be customized
- Steel material we use is high strength low alloy steel Q345.
- Welded by automatic submerged-arc process. Complete chassis shot blasting to clean rust and remove welding stress
- Different thickness of diamond pattern floor plate is optional
- Axles could be optional for German type or American type
- Suspension is optional for mechanical suspension, air suspension



### Advantage of 2 Axles 20ft Flatbed Container Transport Semi Truck Trailer

- 1. Mature technology, could be produced in large quantity at competitive cost
- 2. Lighter weight with high strength to transport container

www.ultratontrailer.com



# Foshan Ultraton Engineering Machinery Co., Ltd


3. Shipped both by container, or RORO, bulk shipment.

4. Advanced manufacturing equipment and mature workmanship to ensure outstanding performance

5. Fast response and flexible service from our professional team

6. Distinct location to get full range support on delivery and manufacturing

7. The long term tenet of Ultraton as one of the standout <u>semi trailer manufacturers</u> to be your reliable partner bringing you Greater value makes you worry free on after sales service



Tare Weight(KG)4200KGLoading Capacity(KG)40000KGDimension(mm)9000*2500*1500Main BeamThe height of the beam is 500 mm, upper Flange is14mm, Lower Flange is 14mm,Web is 8mm.Kingpin2" / 3.5", Welded/Bolt-InLanding GearStandard 28Ton , FUWA BrandAxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringStandard FUWA Brand / ULTRATON BrandBrake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS.	Technical Parameter	2 Axles 20ft Flatbed Container Transport Semi Truck Trailer
Loading Capacity(KG)40000KGDimension(mm)9000*2500*1500Main BeamThe height of the beam is 500 mm, upper Flange is 14mm, Lower Flange is 14mm,Web is 8mm.Kingpin2" / 3.5", Welded/Bolt-InLanding GearStandard 28Ton , FUWA BrandAxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringStandard FUWA Brand or HuaJing BrandLeaf SpringStandard FUWA Brand/ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandDiftional : BPW Brand or HuaJing BrandSuspensionStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Tare Weight(KG)	· · ·
Dimension(mm)9000*2500*1500Main BeamThe height of the beam is 500 mm, upper Flange is 14mm, Lower Flange is 14mm,Web is 8mm.Kingpin2" / 3.5",Welded/Bolt-InLanding GearStandard 28Ton , FUWA BrandAxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringStandard FUWA Brand/ULTRATON BrandUeaf SpringStandard FUWA Brand/ULTRATON Brand90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS.24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		40000KG
Main BeamThe height of the beam is 500 mm, upper Flange is14mm, Lower Flange is 14mm,Web is 8mm.Kingpin2" / 3.5",Welded/Bolt-InLanding GearStandard 28Ton , FUWA BrandAxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringStandard FUWA Brand or HuaJing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		9000*2500*1500
Kingpin2" / 3.5" ,Welded/Bolt-InLanding GearStandard 28Ton , FUWA BrandAxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or Hualing BrandOptional : BPW Brand or Hualing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringOptional : BPW Brand or Hualing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		The height of the beam is 500 mm, upper Flange is14mm,
Landing GearStandard 28Ton , FUWA BrandAxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringStandard FUWA Brand/ULTRATON BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		
AxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringOptional : BPW Brand or HuaJing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Kingpin	2" / 3.5" ,Welded/Bolt-In
AxleStandard FUWA Brand / ULTRATON BrandOptional : BPW Brand or HuaJing BrandSuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandLeaf SpringOptional : BPW Brand or HuaJing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Landing Gear	Standard 28Ton , FUWA Brand
SuspensionMechanical Suspension/Air Suspension,Standard FUWA Brand/ULTRATON BrandCoptional : BPW Brand or HuaJing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Axle	
Brand/ULTRATON BrandOptional : BPW Brand or Hualing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve, OPTIONS: ABS.24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		Optional : BPW Brand or HuaJing Brand
Optional : BPW Brand or Hualing BrandLeaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Suspension	Mechanical Suspension/Air Suspension, Standard FUWA
Leaf SpringStandard FUWA Brand/ULTRATON Brand 90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		Brand/ULTRATON Brand
90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		Optional : BPW Brand or HuaJing Brand
90mm*16*7 or 90*16*8Brake systemDual Air Brake (Drum) System, With Inter-Locking Device.WABCO RelayElectrical SystemEmergency Valve, OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Leaf Spring	Standard FUWA Brand/ULTRATON Brand
Device.WABCO RelayElectrical SystemEmergency Valve,OPTIONS: ABS.24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		90mm*16*7 or 90*16*8
Electrical SystemEmergency Valve,OPTIONS: ABS. 24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Brake system	Dual Air Brake (Drum) System, With Inter-Locking
24 Volt LED Electrical System In Accordance To The Standard, With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		Device.WABCO Relay
With 7-Core Adaptor For Tractor.Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Electrical System	Emergency Valve, OPTIONS: ABS.
Tire12.00R22.5 Tubeless,8 UnitsRim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		24 Volt LED Electrical System In Accordance To The Standard,
Rim9.0*22.5,8 UnitsShot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		With 7-Core Adaptor For Tractor.
Shot Blasting & PaintingShot Blasting and Sanding Treatment . Two Coat Of Anti Corrosion Primer and Two Coat Of Finish PaintingMud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Tire	12.00R22.5 Tubeless,8 Units
Corrosion Primer and     Two Coat Of Finish Painting     Mud Guard   Fabricated Mud Guard 4 nos     Tool Box   1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Rim	9.0*22.5,8 Units
Two Coat Of Finish Painting   Mud Guard Fabricated Mud Guard 4 nos   Tool Box 1 Standard (The Tool Box Size Can Be Tailored To Suit Your	Shot Blasting & Painting	Shot Blasting and Sanding Treatment . Two Coat Of Anti
Mud GuardFabricated Mud Guard 4 nosTool Box1 Standard (The Tool Box Size Can Be Tailored To Suit Your		Corrosion Primer and
Tool Box 1 Standard (The Tool Box Size Can Be Tailored To Suit Your		Two Coat Of Finish Painting
, , , , , , , , , , , , , , , , , , ,	Mud Guard	Fabricated Mud Guard 4 nos
Needs)	Tool Box	1 Standard (The Tool Box Size Can Be Tailored To Suit Your
		Needs)

inquiry@ultratontrailer.com



Foshan Ultraton Engineering Machinery Co., Ltd

Container Locks	4/8/12 Screw type	
Spare Tire Carrier	Equipped one sets per chassis without spare tire.	
Front Baffle	According To Customer's Requirement	
We Can Build The Trailer According To Customer's Design And Requirement.		

### Application of 2 Axles 20ft Flatbed Container Transport Semi Truck Trailer

Ultraton's <u>2 axles 20ft Flatbed Semi Trailer</u> could be used as a basic model to transport standard 20ft container in ports or from site to site on road. Suitable for logistic company, terminal ports, shipping lines, forwarders, truck manufacturer

